



CLOUD VIDEO SURVEILLANCE

# Eagle Eye Cloud VMS Camera & Accessory Catalog





## COMPANY OVERVIEW

# Smart, Simple, Cloud Video Surveillance for Your Business

Your security system should not only protect your people and property, it should also provide insight to help your business grow and thrive. It's Eagle Eye Networks mission to help you do just that.

We're leaders in delivering the power, flexibility, and cost-savings of cloud technology to the video surveillance market, helping you improve operations and enhance customer service, all while keeping an eye on what truly matters.

Whether you run a small business, global enterprise, or something in-between, you need a video solution capable of adapting to your needs – today and tomorrow. The Eagle Eye Cloud Video Management System (VMS) simplifies video surveillance through the flexibility of cloud paired with the convenience of easy, affordable installation and remote management.

## TABLE OF CONTENTS

|                                       |    |
|---------------------------------------|----|
| CAMERAS                               | 3  |
| ENCODER                               | 7  |
| ACCESSORIES                           | 7  |
| Eagle Eye SD Cards                    | 8  |
| Eagle Eye Junction Boxes              | 8  |
| Eagle Eye Wall Arms                   | 9  |
| Eagle Eye Pendants and<br>Poll Mounts | 9  |
| Eagle Eye Corner Mounts               | 9  |
| Eagle Eye Camera Caps                 | 10 |
| ACCESSORY SELECTION                   | 11 |





DON'T LOSE YOUR INVESTMENT, CHOOSE YOUR INVESTMENT





# Eagle Eye Cameras

Don't get locked into any one camera brand or model, or get forced into ripping and replacing your existing cameras. The Eagle Eye Cloud VMS supports more than 4,000 cameras from all the leading manufacturers, but if you're looking to buy new cameras, Eagle Eye Cameras offer a secure, plug-and-play installation.

Camera models are suitable for indoor and outdoor use for a wide range of applications. The cameras come pre-configured to securely operate with the Eagle Eye Cloud Security VMS and Eagle Eye CameraManager.


|                           | CAMERA DB10   | CAMERA DB11  | CAMERA DB12   | CAMERA DB13  |
|---------------------------|---|--|---|--|
|                           |    |   |    |   |
| <b>Description</b>        | Ultra-lowlight, indoor/ outdoor, waterproof mini bullet.  | Ultra-lowlight, indoor/ outdoor, waterproof mini bullet.   | High-performance, indoor/outdoor, waterproof mini bullet.   | High-performance, indoor/outdoor, waterproof bullet.   |
| <b>Resolution</b>         | 4 Mega Pixels   | 4 Mega Pixels  | 8 Mega Pixels   | 8 Mega Pixels  |
| <b>Lens</b>               | 2.8mm   | 2.7 – 13.5mm Motorized Lens  | 2.8mm   | 2.7 - 13mm Motorized Lens  |
| <b>Night Vision</b>       | Smart IR LEDs with up to 30m range  | Smart IR LEDs with up to 40m range   | Smart IR LEDs with up to 30m range  | Smart IR LEDs with up to 40m range   |
| <b>Dynamic Range</b>      | WDR (120dB) and HLC/BLC   | WDR (120dB) and HLC/BLC  | WDR (120dB) and HLC/BLC   | WDR (120dB) and HLC/BLC  |
| <b>Housing</b>            | Durable All Aluminum  | Durable All Aluminum   | Durable All Aluminum  | Durable All Aluminum   |
| <b>Ingress Protection</b> | IP67  | IP67   | IP67  | IP67   |
| <b>Streaming Protocol</b> | Quad RTSP Streams   | Triple RTSP Streams  | Triple RTSP Streams   | Triple RTSP Streams  |
| <b>Applications</b>       | Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms. | Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses. | Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms. | Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses. |

|                           | CAMERA DD07   | CAMERA DD08   | CAMERA DD09   | CAMERA DD10   |
|---------------------------|---|---|---|---|
|                           |    |    |    |    |
| <b>Description</b>        | Ultra-lowlight, indoor/<br>outdoor, waterproof<br>vandal dome.  | Ultra-lowlight, indoor/<br>outdoor, waterproof<br>vandal dome.  | High-performance,<br>indoor/outdoor,<br>waterproof vandal dome.   | High-performance,<br>indoor/outdoor,<br>waterproof vandal dome.   |
| <b>Resolution</b>         | 4 Mega Pixels   | 4 Mega Pixels   | 4 Mega Pixels   | 8 Mega Pixels   |
| <b>Lens</b>               | 2.8mm   | 2.7 – 13.5mm Motorized Lens   | 2.7 – 13.5mm Motorized Lens   | 2.8mm   |
| <b>Night Vision</b>       | Smart IR LEDs with up to<br>30m range   | Smart IR LEDs with up to<br>30m range   | Smart IR LEDs with up to<br>30m range   | Smart IR LEDs with up to<br>30m range   |
| <b>Dynamic Range</b>      | WDR (120dB) and HLC/BLC   | WDR (120dB) and HLC/BLC   | WDR (120dB) and HLC/BLC   | WDR (120dB) and HLC/BLC   |
| <b>Housing</b>            | Durable All Aluminum  | Durable All Aluminum  | Durable All Aluminum  | Durable All Aluminum  |
| <b>Ingress Protection</b> | IP67 & IK10   | IP66 & IK10   | IP67 & IK10   | IP67 & IK10   |
| <b>Streaming Protocol</b> | Quad RTSP Streams   | Triple RTSP Streams   | Triple RTSP Streams   | Triple RTSP Streams   |
| <b>Applications</b>       | Best for small indoor areas:<br>stock room, lobby, hallways,<br>elevators, IT closets,<br>storage rooms, entrances,<br>interview rooms. | Best for modest outdoor<br>areas or large indoor areas:<br>Small Parking lots, fields,<br>parking garages, work<br>yards, back yards, outdoor<br>entrances, warehouses. | Best for modest outdoor<br>areas or large indoor areas:<br>Small Parking lots, fields,<br>parking garages, work<br>yards, back yards, outdoor<br>entrances, warehouses. | Best for small indoor areas:<br>stock room, lobby, hallways,<br>elevators, IT closets,<br>storage rooms, entrances,<br>interview rooms. |

|                           | CAMERA DD11  | CAMERA DF04  | CAMERA DM08   | CAMERA DT01  |
|---------------------------|--|--|---|--|
|                           |   |   |    |   |
| <b>Description</b>        | High-performance, indoor/outdoor, waterproof vandal dome.  | Indoor/outdoor, fisheye with integrated microphone, 360° view.   | High-performance, indoor/outdoor, mini dome with integrated microphone.   | High-performance, indoor/outdoor, turret with integrated microphone.   |
| <b>Resolution</b>         | 8 Mega Pixels  | 12 Mega Pixels   | 4 Mega Pixels   | 4 Mega Pixels  |
| <b>Lens</b>               | 3.3 - 12mm Motorized Lens  | Fixed 1.8mm  | 3.6mm or 2.8mm  | Fixed 2.8mm Lens   |
| <b>Night Vision</b>       | Smart IR LEDs with up to 30m range   | Smart IR LEDs with up to 15m range   | IR LEDs with up to 15m range  | Smart IR LEDs with up to 30m range   |
| <b>Dynamic Range</b>      | WDR (120dB) and HLC/BLC  | DWDR   | WDR (120dB) and HLC/BLC   | DWDR and HLC/BLC   |
| <b>Housing</b>            | Durable All Aluminum   | Durable All Aluminum   | Durable All Aluminum  | Durable All Aluminum   |
| <b>Ingress Protection</b> | IP66 & IK10  | IP66   | IP66  | IP66   |
| <b>Streaming Protocol</b> | Triple RTSP Streams  | Triple RTSP Streams  | Triple RTSP Streams   | Triple RTSP Streams  |
| <b>Applications</b>       | Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses. | Best for medium size open areas: hallways, intersections, lobbies, and retail. Optimal view is 25 ft radius from camera placement. | Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms. | Best for modest outdoor areas or large indoor areas: small parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses. |



|                           | CAMERA DT02  | CAMERA DT03   | CAMERA DX01  | CAMERA DZ04   |
|---------------------------|--|---|--|---|
|                           |   |    |                      |  |
| <b>Description</b>        | High-performance, indoor/outdoor, turret with integrated microphone.   | Ultra low light with integrated warm light LEDs, indoor/outdoor, turret with integrated microphone.   | High-performance, indoor/outdoor, 180° stitched panoramic bullet with integrated microphone.           | High-performance, indoor/outdoor, weatherproof dome.                                |
| <b>Resolution</b>         | 4 Mega Pixels  | 4 Mega Pixels   | 8 Mega Pixels  | 5 Mega Pixels   |
| <b>Lens</b>               | 2.7 - 13.4mm Motorized Lens  | 2.8mm Fixed Lens  | 2.8mm Fixed Lens   | 5.3 - 159mm Motorized Lens  |
| <b>Night Vision</b>       | Smart IR LEDs with up to 40m range   | Smart IR LEDs with up to 40m range  | LED illumination provides warm light at a distance up to 20m for 24/7 full color images                | Up to 150m  |
| <b>Dynamic Range</b>      | WDR (120dB) and HLC/BLC  | True WDR  | True WDR   | True WDR > 120dB  |
| <b>Housing</b>            | Metal + Plastic  | Metal + Plastic   | Metal  | Metal   |
| <b>Ingress Protection</b> | IP66   | IP66  | IP66   | IP66 & TVS4000V   |
| <b>Streaming Protocol</b> | Triple RTSP Streams  | Triple RTSP Streams   | Triple RTSP Streams  | Triple RTSP Streams   |
| <b>Applications</b>       | Best for modest outdoor areas or large indoor areas: small parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses. | Best for outdoor applications where low light color performance is required. Can also produce a color image in no light scenarios by using the warm light LEDs. | Best for building perimeters or large open areas like parking lots, fields, road ways, and warehouses. | Best for large areas like parking lots, fields, road ways, and warehouses.          |

# Eagle Eye Encoder

|                          |  | EC01  |
|--------------------------|--|---|
| <b>Camera Input</b>      | 16 Channel BNC   |  |
| <b>Input Resolutions</b> | 8 Mega Pixels, 5 Mega Pixels, 4 Mega Pixels, 1080 Pixels, 720 Pixels |   |
| <b>Formats</b>           | AHD, TVI, CVI, CVBS  |   |
| <b>HDMI Output</b>       | 3840×2160, 1920×1080, 1280×1024, 1024×768                            |   |
| <b>Dimensions</b>        | 380 x 159.8 x 51 mm  |   |
| <b>Weight</b>            | 1.6 kg   |   |





# Eagle Eye Camera Accessories

## SD Cards

|                      | EN-SDMD-001  | EN-SDMD-002  |
|----------------------|--|--|
|                      |   |   |
| <b>Description</b>   | Eagle Eye Industrial High Endurance Video microSD Card 32G with built-in sync between SD Card & Eagle Eye Cloud. Continues recording without internet. | Eagle Eye Industrial High Endurance Video microSD Card 64G with built-in sync between SD Card & Eagle Eye Cloud. Continues recording without internet. |
| <b>Compatibility</b> | Eagle Eye Cameras with SD Slot   | Eagle Eye Cameras with SD Slot   |
| <b>Warranty</b>      | 2 Years  | 2 Years  |
| <b>Recording</b>     | Video and audio  | Video and audio  |

## Junction Boxes

|                           | JUNCTION BOX BX004  | JUNCTION BOX BX005   | JUNCTION BOX BX006  |
|---------------------------|---|--|---|
|                           |  |  |  |
| <b>Compatibility</b>      | Please see "Accessory Selection"  | Please see "Accessory Selection"   | Please see "Accessory Selection"  |
| <b>Material</b>           | Aluminum alloy  | Aluminum alloy   | Aluminum alloy  |
| <b>Color</b>              | White   | White  | White   |
| <b>Operating Humidity</b> | 0% - 90% RH   | 0% - 90% RH  | 0% - 90% RH   |
| <b>Load Bearing</b>       | 4 kg (8.82 lb)  | 2 kg (4.4 lb)  | 4 kg (8.82 lb)  |
| <b>Dimensions</b>         | Φ142 × 51 mm (Φ5.6 × 2.0")  | Φ123 × 52 mm (Φ4.84 × 2.05")   | Φ121 × 46 mm (Φ4.76 × 1.81")  |
| <b>Weight</b>             | 0.56 kg (1.23 lb)   | 0.4 kg (0.88 lb)   | 0.4 kg (0.88 lb)  |




|                           | JUNCTION BOX BX007  | JUNCTION BOX BX008  | JUNCTION BOX BX009  | JUNCTION BOX BX011  |
|---------------------------|---|---|---|---|
|                           |  |  |  |  |
| <b>Compatibility</b>      | Please see "Accessory Selection"  | Please see "Accessory Selection"  | Please see "Accessory Selection"  | Please see "Accessory Selection"  |
| <b>Material</b>           | Aluminum alloy  | Aluminum alloy + plastic  | Aluminum alloy + plastic  | Aluminum alloy  |
| <b>Color</b>              | White   | White   | White   | White   |
| <b>Operating Humidity</b> | 0% - 90% RH   | 0% - 90% RH   | 0% - 90% RH   | 0% - 90% RH   |
| <b>Load Bearing</b>       | 4 kg (8.82 lb)  | 3 kg (6.61 lb)  | 3 kg (6.61 lb)  | 3 kg (6.61 lb)  |
| <b>Dimensions</b>         | Φ121 × 46 mm (Φ4.76 × 1.81")  | Φ110 × 37.3 mm (Φ4.33 × 1.47")  | Φ107 × 46 mm (Φ4.21 × 1.81")  | Φ123 × 52 mm (Φ4.84 × 2.05")  |
| <b>Weight</b>             | 0.4 kg (0.88 lb)  | 0.21 kg (0.46 lb)   | 0.34 kg (0.75 lb)   | 0.4 kg (0.88 lb)  |



## Wall Arms

|                           | WALL ARM WA006  | WALL ARM WA007  |
|---------------------------|---|---|
|                           |  |  |
| <b>Compatibility</b>      | Please see "Accessory Selection"  | Please see "Accessory Selection"  |
| <b>Material</b>           | Aluminum alloy  | Aluminum alloy  |
| <b>Color</b>              | White   | White   |
| <b>Operating Humidity</b> | 0% - 90% RH   | 0% - 90% RH   |
| <b>Load Bearing</b>       | 3 kg (6.61 lb)  | 3 kg (6.61 lb)  |
| <b>Dimensions</b>         | 141 × 116.2 × 116.2 mm (5.55 × 4.57 × 4.57")                                      | 201.8 × 120.2 × 167.4 mm (7.94 × 4.73 × 6.59")                                      |
| <b>Weight</b>             | 0.25 kg (0.55 lb)   | 0.85 kg (1.87 lb)   |

## Pendants, Pole Mounts, and Corner Mounts

|                           | PENDANT PE004   | POLE MOUNT 002  | CORNER MOUNT 002  |
|---------------------------|---|---|---|
|                           |  |              |  |
| <b>Compatibility</b>      | Please see "Accessory Selection"  | Please see "Accessory Selection"  | Please see "Accessory Selection"  |
| <b>Material</b>           | Aluminum alloy  | Aluminum alloy + stainless steel  | Aluminum alloy  |
| <b>Color</b>              | White   | White   | White   |
| <b>Operating Humidity</b> | 0% - 90% RH   | 0% - 90% RH   | 0% - 90% RH   |
| <b>Load Bearing</b>       | 3 kg (6.61 lb)  | 4 kg (8.82 lb)  | 4 kg (8.82 lb)  |
| <b>Dimensions</b>         | Φ140 × 264 mm (Φ5.51 × 10.4")   | 130.2 × 46 × 170 mm (5.13 × 1.81 × 6.69")<br>Embrace Hoop Diameter: 130 ~ 152 mm (5.12 ~ 5.98") | 176.5 × 103.3 × 170 mm (6.95 × 4.07 × 6.69")  |
| <b>Weight</b>             | 0.56 kg (1.23 lb)   | 0.41 kg (0.9 lb)  | 0.5 kg (1.1 lb)   |

## Camera Caps

|                           | CAMERA CAP 001  | CAMERA CAP 002   | CAMERA CAP 003  |
|---------------------------|---|--|---|
|                           |  |  |  |
| <b>Compatibility</b>      | Please see "Accessory Selection"  | Please see "Accessory Selection"   | Please see "Accessory Selection"  |
| <b>Material</b>           | Aluminum alloy  | Aluminum alloy   | Aluminum alloy  |
| <b>Color</b>              | White   | White  | White   |
| <b>Operating Humidity</b> | 0% - 90% RH   | 0% - 90% RH  | 0% - 90% RH   |
| <b>Load Bearing</b>       | 3 kg (6.61 lb)  | 3 kg (6.61 lb)   | 3 kg (6.61 lb)  |
| <b>Dimensions</b>         | Φ109.8 × 65 mm (Φ4.32 × 2.56")  | Φ122.8 × 68 mm (Φ4.83 × 2.68")   | Φ145 × 73 mm (Φ5.71 × 2.87")  |
| <b>Weight</b>             | 0.13 kg (0.29 lb)   | 0.17 kg (0.37 lb)  | 0.21 kg (0.46 lb)   |

|                           | CAMERA CAP 004  | CAMERA CAP 005   | CAMERA CAP 006  |
|---------------------------|---|--|---|
|                           |  |  |  |
| <b>Compatibility</b>      | Please see "Accessory Selection"  | Please see "Accessory Selection"   | Please see "Accessory Selection"  |
| <b>Material</b>           | Aluminum alloy  | Aluminum alloy   | Aluminum alloy  |
| <b>Color</b>              | White   | White  | White   |
| <b>Operating Humidity</b> | 0% - 90% RH   | 0% - 90% RH  | 0% - 90% RH   |
| <b>Load Bearing</b>       | 3 kg (6.61 lb)  | 3 kg (6.61 lb)   | 3 kg (6.61 lb)  |
| <b>Dimensions</b>         | Φ118 × 68 mm (Φ4.65 × 2.68")  | Φ122.8 × 70 mm (Φ4.83 × 2.76")   | 99.5 × 99.5 x 75.8 mm (3.92 × 3.92 x 2.98")   |
| <b>Weight</b>             | 0.17 kg (0.37 lb)   | 0.25 kg (0.55 lb)  | 0.19 kg (0.42 lb)   |

MIX AND MATCH COMPATIBLE HARDWARE

# Accessory Selection

